

# VacuForm 400, 600, 900



## Features

- Stainless steel construction
- Integrated with the filling machine
- No hydraulic
- Simple drive unit
- No water
- Programmable in different languages
- Open for optical access and survey during operation and cleaning
- Forming Plates:
  - Automatic positioning
  - Quick changing
- Knock-out cups
  - Heated
- Control Function
  - Accurate portioning under vacuum
  - Speed
  - Stacking
  - Speed of out-feed conveyor belt
  - Hand operation
- Stainless steel pump system
- VacuForm 400 (Contivac 100, Contivac 200)
- VacuForm 600 (Contivac 200, Contivac 400)
- VacuForm 900 (Contivac 400, Contivac 400S)
- Product transport
  - Single
  - Shingling without paper
  - Stacked with paper
- Options
  - Paper feed
  - Cleaning trolley
- Products:
  - Hamburgers
  - Cutlets
  - Nuggets
  - Fish
  - Potato
  - Vegetable products

## VacuForm Patty Former

Model	400	600	900
Maximum speed	50 – 70 strokes/min	50 – 70 strokes/min	50-70 strokes/min
Forming plate thickness	5 – 38 mm	5 – 38 mm	5 – 38 mm
Maximum capacity*	+/- 1600 kg/hr	+/- 2000 kg/hr	+/- 3000 kg/hr
Forming area	400 x 152 mm	600 x 152 mm	900 x 152 mm
Conveyor belt speed	7 – 20 m/min	7 – 20 m/min	7 – 20 m/min
O/A Dimensions (L x W x H)	1950 x 1150 x 1750 mm	1950 x 1150 x 1750 mm	1950 x 1450 x 1750 mm
Conveyor belt dimensions ( C x H1)	665 x 900 – 1000 mm	665 x 900 – 1000 mm	1065 x 900 – 1100 mm
Electrical	6 kW	6 kW	9 kW
Compressed air	7 ltr/min	7 ltr/min	7 ltr/min
Working pressure	4 – 7 bar	4 – 7 bar	4 – 7 bar
Weight	550 kg	580 kg	700 kg

\*Depending on product, portion and weight  
 \*\*All specifications are subject to change without notice



## Technical Specification\*\*



Vane Pump System



Patty Former with Paper



Forming Plate



Conveyor



Multiple Extrusion



Control Panel

We provide technical support and service for all machines that we sell.



2820 East Washington Blvd Los Angeles CA 90023  
 323-268-8514 800-421-6265 323-268-6305 (fax) www.mpbs.com



Since 1938